


OAK

Spring 2019



Artisan
REAL OAK FLOORING

De Marqué
PARQUETRY

PRESTIGE
OAK FLOORING

PRONTO
READY TO GO


by
PREFERENCE
FLOORS



PRESTIGE OAK LATTE



ARTISAN OAK NATURAL CLASSIC
FRONT COVER: PRESTIGE OAK PARANA



PRESTIGE OAK MINK GREY

OAK



PRESTIGE OAK

If you love the look of fine oak flooring then Prestige Oak is the natural choice. Sharing the unrivalled beauty and character of traditional European Oak, Prestige Oak Flooring is a popular choice amongst leading Australian architects and designers. Design flexibility is assured with stunning extra wide planks and an extensive palette of pre-finished natural, and stained décors. The range includes both Uniclic profile for floating installation and Tongue & Groove for a traditional installation.



ARTISAN OAK

The timeless elegance and natural character of European Oak makes it an ideal timber to enhance any interior décor. Our Artisan Oak range provides a palette of natural tones along with contemporary visuals. These colours and textures are enhanced by unique surface treatments and pre-finished with a water based, non-toxic European PU coating. Combining a world renowned patented click locking profile Artisan Oak planks are easy to install providing a no fuss, pre-finished, ready to walk on floor.



PRONTO

Pronto engineered oak planks are manufactured from a rustic grade of sustainable European Oak with a solid Oak wear layer engineered onto a three layer substrate. This trusted method of construction provides a long wearing, stable and durable floor perfectly suited for multi residential, residential and commercial installations. Pronto is presented with a patented click locking profile for floating installations providing fast and cost efficient installation.



DE MARQUÉ PARQUETRY

For centuries, classic residencies and spectacular chateaus have all featured the unique beauty of Oak parquetry. Parquetry formations provide these structures unique character and appeal that has truly stood the test of time. Our De Marqué Parquetry Collection draws on this design cue, featuring Herringbone and Chevron patterns for everyday living. A classic and contemporary palette of pre-finished colours provides wonderful warmth and charm to almost any interior.



PRESTIGE

OAK FLOORING

Our versatile Prestige Oak range includes a selection of widths and thicknesses for a variety of applications.

Available in both traditional Tongue & Groove and the ever popular Unilin click system for fast and convenient installation.

On-trend colours, scratch resistant coatings, Prestige Oak flooring ensures lifetime enjoyment.

EBONY

STOCK PROFILES AVAILABLE



Prestige Oak Click is designed to be installed as a floating installation utilising the click together method of assembly over an acoustic underlay incorporating a Moisture Barrier.

Our Click stock range is **190 x 15/4 mm**. The click together profile is also suitable with a direct fix adhesive method of installation. Our Tongue & Groove (T&G) **220 x 21 mm** Wide Plank is ideally suited for direct fix adhesive method of installation.


Both methods of installation require skilled installation techniques and we highly recommend you engage only qualified install professionals. Please check with your reseller or the helpful site at ATFA (Australian Timber Flooring Association) to locate a specialist installer.

Other widths & thicknesses are available for contract orders, minimum volumes will apply, please check for availability.

PRESTIGE OAK CLICK



PRESTIGE OAK T&G





DETAILS AND THE BEAUTY

The unique specifications of Prestige Oak flooring make it ideal for installation throughout homes, apartments or commercial applications with the exception of wet areas such as bathrooms and laundries.

- ▀ Engineered construction, real European Oak. Easy care and maintenance, allergy free.
- ▀ Pre-finished European water-based UV lacquer. Superior matte wear resistant coating, timeless look.
- ▀ Variation in specific colours and grade may include: black & mineral streaks, sapwood, ray flecks, filled splits & knots, checks, and natural batch colour toning. These are all natural characteristics of European Oak.
- ▀ VOC Emissions: <E1. Below World Health Organisation Levels. 'CE' label is the manufacturer's declaration that the product meets the European conformity code.
- ▀ Fire & Slip test certified to current Australian Standards. Suitable for install over Hydronic in-slab heating only.

25 Year Limited (Lifetime) Structural Warranty | 20 Years Limited Residential Wear Warranty | 5 Years Limited Commercial Structural & Wear Warranty



CANNES



ENGINEERED FOR QUALITY

Creating a timber floor that shows character starts with an emphasis on quality. Engineered floors are designed to provide excellent characteristics un-matched by solid wood floors. Our Prestige Engineered Oak will have a higher resistance to moisture fluctuations than solid timber making it less susceptible to plank deformation caused by shrinkage, cupping, warping and bowing. When installed correctly your Engineered Oak floor will display the same look, feel and benefits normally associated with a solid timber floor. Prestige Oak is manufactured utilising resource efficient engineering processes using our valuable Oak resource where it's needed most, and that's the wear layer.

- Multi-ply Hardwood Construction
- Grade ABCD Janka Hardness 5.5 – 6.0kN
- 190 x 15 /4 mm Click for floating install & T&G for direct fix
- 220 x 21/6 mm T&G for Direct Fix Install
- Set Length with nested shorts
- Micro Bevel 4 sides & Light Brushed Surface
- VOC Free Water Based Matte Coating E1
- Australian Fire & Slip test certified
- T&G & Click Stair Nosing Available
- Suitable for Hydronic in-slab Heating Only

25 Year Limited (Lifetime) Structural Warranty

20 Years Limited Residential Coating Warranty


**5 Years Limited Commercial Structural
& Coating Warranty**



CANNES



CANNES




PARANA

The design versatility
of Oak, let your
imagination run wild.




PRESTIGE OAK


190 x 15/4mm. Click Profile



Avola Natural




Castle Grey




Chesnut




Dark Brown




Ebony




Espresso




Grey Wash




Heritage Grey



Hex Grey



Iron Grey




Latte




Liquorice

PRESTIGE OAK


190 x 15/4mm. Click Profile




Limewash




Marble




Parana



Storm




Straw



Tan



Vanilla




White Sands


*Visual décors of
warmth & charm*

PRESTIGE OAK


220 x 21/6mm. T&G Profile




Aged Oak




Black Fox




Bleached Driftwood




Cannes




Champagne




Chardonnay



Crema




Derby Brown



Dover Grey



French Brown




Glacier




Grey Mist

PRESTIGE OAK


220 x 21/6mm. T&G Profile




Grigio




Merlot




Mink Grey



Moonlight




Moscato




Semillon



Slate



Tokay



White Wash

*Colours & textures
drawn from nature*

Images for illustrative purposes only, batch and grade variations will occur.

Ranges & Colours are updated throughout the year, please check www.preferencefloors.com.au or our local office contacts for availability.

Artisan.

REAL OAK FLOORING



ROMANDIE

ARTISAN OAK, A NATURAL CHOICE

Our Artisan range is produced from sustainably managed timber resources and manufactured with non-toxic materials. Engineered construction for stability, strength and durability.

With confidence you can specify Artisan Oak flooring knowing that it will not compromise our valuable forest environment or impact on our general well-being.

The Artisan range is available in two widths,
Classic Width 190 mm and our Extra Wide 240 mm.





OXFORD GREY



NATURAL CLASSIC



OXFORD GREY

bespoke colours for urban design


Artisan Oak, wide plank visuals, wonderful décors and the convenience of a patented locking system, what more could you ask for?

Easy to install providing a no fuss, pre-finished, ready to walk on floor.


**The Artisan range is available in two widths,
Classic Width 190 mm and our Extra Wide 240 mm.**

Artisan Oak
190 x 14 mm
Click Profile
Classic Width


Images for illustrative purposes only,
batch and grade variations will occur.




Biarritz




Chantilly




Chanterelle




Provence




Naturalle



Cottonwood



Oxford Grey



Woodlands




PROVENCE

Artisan Oak
240 x 14 mm
Click Profile
Extra Wide


Images for illustrative purposes only,
batch and grade variations will occur.

DETAILS AND THE BEAUTY

- ♣ Genuine Oak, Natural product
- ♣ Engineered construction for stability
- ♣ Easy to install, minimal care & maintenance
- ♣ Suitable for new construction or renovation projects
- ♣ Contemporary colour palette including natural visuals
- ♣ Australian warranty and customer service support
- ♣ Appealing matte low sheen coating




Natural Classic



Montreux



Brittany Grey



Romandie

OAK



ENGINEERED FOR QUALITY

- Grade ABCD Janka Hardness 5.5-6.0kN
- Patented Click
- Micro Bevel 4 sides
- Set Length with nested shorts
- 190 x 14 mm @ 240 x 14 mm
- Light Brushed Surface
- VOC Free Water Based Matte Coating E1
- Australian Fire & Slip test certified
- Click Stair Nosing Available
- Suitable for Hydronic in-slab Heating Only

25 Year Limited (Lifetime) Structural Warranty

20 Years Limited Residential Coating Warranty

**5 Years Limited Commercial Structural
& Coating Warranty**

COTTONWOOD

PRONTO

READY TO GO



ENGINEERED FOR QUALITY

- 3 Layer construction
- Grade ABCD Janka Hardness 5.5 – 6.0kN
- Patented Valinge 5g Click
- Micro Bevel 4 sides
- Set Length with nested shorts
- 190 x 13.5 mm
- Light Brushed Surface
- VOC Free Water Based Matte Coating E1
- Australian Fire & Slip test certified
- Click Stair Nosing Available
- Suitable for Hydronic in-slab Heating Only

25 Year Limited (Lifetime) Structural Warranty

20 Years Limited Residential Coating Warranty

5 Years Limited Commercial Structural & Wear Warranty

SPINDRIFT

ready to go

Pronto is all about speed and efficiency with the cost conscious consumer in mind.


With a tight palette of light to dark colours the range is designed to maximise quality without compromising the performance of the product. The cost of installation is kept to a minimum with the fuss free, easy to install patented click system.

Pronto ready to go, ideally suited for residential or multi-residential living.




Pronto 190 x 13.5 mm Click Profile


Images for illustrative purposes only,
batch and grade variations will occur.




Santorini




Regal Oak




Portofino



Spindrift




Ponderosa



Chicory

De Marqué

PARQUETRY



SAUVIGNON



SAUVIGNON

HERRINGBONE & CHEVRON PARQUETRY

If looking to make a spectacular design statement our De Marqué pre-finished parquetry is a smart move.

The engineered construction provides dimensional accuracy and stability with a wear layer designed to last for centuries. Presented with a universal T&G system for direct adhesive installation only. Both Chevron and Herringbone patterns are available in a range presented with classic décors of subtle charm that's sure to make an impact. De Marqué parquetry will definitely deliver a sense of calm and beauty into your life.

*Classic look,
amazing impact!*

Beautiful décors,
inspiring design.




Herringbone

600 x 120
x 15/4 mm (T&G)

600 x 120
x 21/6 mm (T&G)


Raw also available.
Images for illustrative purposes only,
batch and grade variations will occur.




Riesling




Sauvignon




Cabernet




Cognac



Ash Grey



Vintage




Dark Brown

Chevron


600 x 90
x 21/6 mm (T&G)

Raw also available.


Images for illustrative purposes only,
batch and grade variations will occur.




Cannes




Champagne



Semillon



Mink Grey



Dark Brown

For specialised widths & colours please check for availability, minimum quantities will apply.

Ranges & Colours are updated throughout the year, please check www.preferencefloors.com.au or our local office contacts for availability. 25



ENGINEERED FOR QUALITY

- Multiply Hardwood Construction
- Grade ABCD Janka Hardness 5,5 – 6.0kN
- Universal T&G Profile
- Micro Bevel 4 sides
- Set Length
- Light Brushed Surface
- VOC Free Water Based Matte Coating E1
- Australian Fire & Slip test certified
- T&G Stair Nosing Available
- Suitable for Hydronic in-slab Heating Only

25 Year Limited (Lifetime) Structural Warranty
20 Years Limited Residential Coating Warranty
5 Years Limited Commercial Structural & Wear Warranty



SAUVIGNON



STAIR NOSING

Both Tongue & Groove & Click Stair nosing is available to support our range of Engineered Oak products.

Stair nosing can be supplied directly from Preference Floors to suit your colour selection or a Reseller may offer these directly from a third party manufacturing to suit local building regulations.

If stairs are involved in your project it is wise to spend time discussing this matter prior to purchase. These images are for illustrative purposes only.



T&G Stair Nosing




Click Stair Nosing

TRIMS & SCOTIA

An extensive range of Scotia colours and Aluminium floor trims are available. These elements form an integral part of all floor installations and especially when floating installations are required.

As per our warranty guidelines, all floating installations will require perimeter expansion and transition trims. It is wise to spend time discussing trim requirements prior to purchase. Some example images below.



Reducer



U Channel




Expansion / Transition

UNDERLAYS

For all floating installations a quality acoustic underlay incorporating a moisture barrier film is required to deliver an optimum outcome. The 3 options available from Preference Floors provide varying price points all meeting National Construction Code (NCC) / Building Code of Australia (BCA) standards for Residential & Multi-Residential construction.

For specific Body Corporate or residential applications please consult with your building or design professional for guidance to make sure your requirements are satisfied. Acoustic test data for each product is available on request.

1. **Standard White Acoustic 20dB**
- Residential Use
2 mm PE Water Resistant Film with overlap for tape. 20 & 50m2 Rolls available, Width 1 Metre.
2. **Ultra Green Acoustic 20 dB**
- Residential & Multi Res Use
2 mm High Compression XPE Foam & PE Water Resistant Film with overlap for tape. 20 m2 Rolls available, Width 1 Metre.
3. **Natural Cork Acoustic 20 dB – Residential & Multi-Res Use**
2 mm High Density Cork inc. PE Water Resistant Film with overlap for tape.
10 m2 Rolls available, Width 1 Metre.



RECOMMENDED CLEANING PRODUCTS

Proper maintenance is often the most overlooked aspect of a timber flooring project. Preventative maintenance includes the installation of adequate mats at all entrances and felt protectors on furniture legs to prevent scratching. On-going maintenance includes proper cleaning methods and use of professional cleaning solutions and equipment.

Bona and Loba products are readily available from specialist timber floor and carpet resellers.



A full range of non-toxic timber floor care products are available.

Contact Loba Australasia on 03 9460 3444 for reseller locations near you.



A full range of non-toxic timber floor care products are available.

Contact Bona Australia on 03 9543 4399 for reseller locations near you.



Methods of engineered plank construction lay-up


The manufacturing of engineered flooring is designed to be more resource efficient using up to 2/3 less of our valuable Oak resource when compared to solid timber floors.

Pre-finished Engineered flooring is dimensionally more stable than solid timber flooring enabling quicker installation with less site related trades to complete the flooring installation.

The two popular methods of engineered construction lay-up include, Multi-ply (Prestige & De Marqué Oak) & 3 Layer (Artisan & Pronto). Both manufacturing methods of construction have proven to be highly reliable over many decades of use.

Multi-ply

Provides a core usually manufactured from mixed hardwood with each veneer (approx. 2mm) running in an alternate direction to provide enhanced radial and longitudinal stability. The wear layer of solid oak is then bonded to the top of the multi-ply core.



3 Layer

For the 3-Layer product the method is similar. The construction lay-up comprises only 3 layers of thicker veneer (lamella) with each layer bonded in an alternate direction for stability. The core of these 3 layers will generally feature small individual pieces of timber (lamella) that are bonded together and placed in the alternate direction to both the top and bottom layers. The solid oak is used as the top visual wear layer.

What to look for

Selection Process

Oak is a natural product and due to the many facets involved in the manufacturing process, each batch, whilst reasonably consistent, will display possible grade and colour batch variations. Quality guidelines are established with our manufacturing partners to set boundaries on variations of colour and grade.

Importantly, always check and confirm your selection when your final purchase is being made. The samples are just that, they are a reflection of one piece of nature at a given time.

Store samples will often deepen or lighten depending on the surface colour and exposure to both direct and indirect UV.

Pre-installation

To avoid unwanted surprises please make sure the batch you received at site is consistent with the specification before installation. Ideally make sure someone checks the colour prior to installation. Do not assume your reseller or installer has checked the colour before delivery to site.

It's easy to assess an issue at this stage and fix any obvious errors, in many examples the site installer may have no idea what was originally expected.

Don't take a risk, open a few cartons to satisfy yourself, if in doubt make immediate contact with your point of purchase.

A new floor installed over an existing floor that has squeaks and movement etc. will not fix structural sub-floor problems.

The sub-floor in both new and or existing construction requires careful assessment to make sure the new floor is suitable for installation.

Remedial activities such as levelling, re-fixing joist and bearers, replacing rotten timber are common considerations when tackling new floor projects.

A flat, secure and dry substrate is essential to achieve a quality outcome.

Installation Methods

Installation methods include both Tongue & Groove Direct Fix method and Click assembly for floating installations.

Both methods are excellent however cost & time are the usual issues for consideration. T&G Direct Fix requires a higher budget and will take longer to install. The Direct Fix method of installation will provide an improved acoustic outcome and feel along with minimal expansion requirements.

Patented Click floating installations are very popular because they are a convenient and cost effective method for modern construction. To improve acoustic performance they will require a quality 2 mm Acoustic Underlay with a moisture vapour barrier to improve transmission sound, impact noise and impede moisture ingress.

Most importantly Click floating installations will require perimeter and room to room expansion / transition trims to break the individual room. They are recommended in our installation guides and if left out by the installer will impact on the floor performance and our warranty provisions. Please discuss this matter when talking with your reseller or designer.

Care & Maintenance

For all engineered oak flooring correct maintenance and cleaning is required to keep your floor looking great. Preventative maintenance includes the installation of quality mats at all entrances and felt protectors on furniture legs to prevent scratching. If other trades are still active at the site it's wise to place a protective covering over the floor whilst construction continues. This should avoid site related damage. Do not tape covering directly to surface coating. Do not leave protective covering in-situ for an extended period of time. Humidity will build up under the floor protective covering resulting in damage to the floor coating. Our coating warranty will not cover this type of damage.

On-going maintenance includes proper cleaning methods and use of protective cleaning products to keep the floor looking good. A correctly maintained timber floor should almost never need to be sanded back to bare timber. Avoid using any generic floor cleaning solutions regularly sold as Floor Cleaner. Generic floor cleaning solutions will damage the floor coating. Bona or Loba floor care products are a safe and reliable way to keep your floor in great shape.

OAK



**Preference Floors
Adelaide**
t +61 8 8262 2774
sa@preferencefloors.com.au

**Preference Floors
Perth**
t +61 8 9471 7785
wa@preferencefloors.com.au

**Preference Floors
Brisbane**
t +61 7 3875 1688
qld@preferencefloors.com.au

**Preference Floors
Sydney**
t +61 2 9738 1188
sales@preferencefloors.com.au

**Preference Floors
Melbourne**
t +61 3 9794 5111
vic@preferencefloors.com.au

www.preferencefloors.com.au